

AAPW-70 SERIES

FEATURES

- Rugged parts tree allows for unique positioning of parts to be cleaned.
- Dual gas shocks dampen lid opening to prevent shell damage.
- Heavy duty 1/2" rust proof polyethylene shell construction provides energy efficient thermal barrier against heat loss.
- Removable heavy-duty parts basket supports up to 500 lbs.
- Optional small parts basket keeps small parts from getting lost.
- Oil skimmer with programmable 7 day timer keeps oil and grease from accumulating in sump.
- Removable chip tray allows for easy access to sump for cleaning, and prevents parts from falling out of reach.
- Optional flow through brush allows for detail cleaning of parts.
- Automatic low level shut down prevents heater damage due to exposure to air.
- Adjustable 0-30 minute wash timer automatically shuts off pump when cover is opened.
- Thermostatically controlled operating temperature at up to 175°F ensures parts come clean and dry quickly.
- Optional automatic water fill and detergent injector ensures regulated detergent concentration injection and maintains liquid level.
- Safety door switch automatically shuts off pump when cover is opened.



Model	Aqueous / Solvent	Load Orientation	GPM	PSI	Operation	Fluid Capacity	Basket Dimensions	Working Height	Load Capacity	Volts/Phase/Amps
AAPW-70D	Aqueous	Top-Load	60	26	Automatic	45 gal.	30"L x 22"W	21"T	500 lbs.	120 / 1 / 15
AAPW-70A	Aqueous	Top-Load	60	26	Automatic	45 gal.	30"L x 22"W	21"T	500 lbs.	220 / 1 / 27

We Know How to Get Things **CLEAN**