



BARRACUDA

SNG Series - Hot Water, Electric Powered, NG Fired, V-Belt, Stationary Pressure Washer

Standard Features

- Rugged powder coated steel frame, enclosed pump/motor compartment and electrical compartment w/hinged lid
- Frame Dimensions: 46" L x 27" W x 50" H;
8.0 GPM Models: 48" L x 31" W x 53" H
- Super efficient schedule 80 coil with stainless steel coil wrap
- LP/NG electronic ignition and 24VAC controls
- Commercial/Industrial grade motors
- Low speed V-belt driven pump
- Adjustable thermostat, safety pressure relief valve, hour meter, soap solenoid with panel mount switch and auto start with adjustable time delay shutdown
- **NOTE: PROFESSIONAL ELECTRICAL, GAS & EXHAUST INSTALLATION REQUIRED**

Standard Accessories

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose with quick connects
- Adjustable high pressure chemical metering system
- 4 color-coded QC spray nozzles

Available Options

- 10" Draft Diverter - Fits all models except 8 GPM models
- 12" Draft Diverter - Fits 8 GPM models only
- Individual Remote Station including Start/Stop/Burner/Soap Functions with Indicator Lights



SNG4020-BGA

Model No.	GPM	PSI	Drive	HP	Electric	Pump
SNG4020-BGA	4.0	2000	V-Belt	5.0	230V/1P/25A	GP
SNG4030-BGA	4.0	3000	V-Belt	7.5	230V/1P/36A	GP
SNG4030-BGB	4.0	3000	V-Belt	7.5	230V/3P/25A	GP
SNG5020-BHA	5.0	2000	V-Belt	7.5	230V/1P/36A	HP
SNG5030-BHA	5.0	3000	V-Belt	10.0	230V/1P/42A	HP
SNG5030-BHB	5.0	3000	V-Belt	10.0	230V/3P/34A	HP
SNG5030-BHC	5.0	3000	V-Belt	10.0	460V/3P/18A	HP
SNG8030-BGC	8.0	3000	V-Belt	15.0	460V/3P/20A	GP

