


makes a difference



Pressure Washer Parts & Accessories 2015



1150 Davis Road, Suite J • Elgin, IL 60123 (800) 788-8867 • info@lorchem.com www.lorchem.com

We Know How To Get Things CLEAN

Legacy Undercarriage Cleaner



Legacy is proud to offer the Undercarriage Cleaner, an ideal way to clean under vehicles and heavy equipment.

- No more crawling under a vehicle
- Simply connect to your hot or cold water pressure washer
- Easy to handle and maneuver
- Removes road grime, fuel and oil contaminants
- Removes snow sludge and ice
- Provides a clean working environment for technicians
- Stainless-steel rotating assembly built to withstand pressures up to 4000 PSI and 250°F
- 5.5" required clearance
- Four nozzles: (2) 0° #2.0, (2) 25° #2.0





Part #	Description
Part #	Description
8.749-303.0	Undercarriage Cleaner



Whisper Wash Flat Surface Cleaners

- · Saves labor, fuel and water
- · Eliminates overspray and zebra striping
- · Use with conventional pressure washers
- . Use with cold or hot water
- Balanced spray bar
- Quick connection
- 2,000-4,000 PSI

Driveways

Sidewalks

School yards

• 2500 RPM

Applications:

- · Service stations
- · Pool and patio decks

The "Maxima 36" · Portable breakaway handle

- · Warehouse floors
- · Loading docks
- · Parking lots

• 212°F • 4-10 GPM • 2500 RPM · Dimensions: Cover: 36" Handle: 77" · Weight 37 lbs

- · Public facilities
- Restaurants
- Gondolas
- · Stadiums Marina docks



Part #	Original No.	Description
B.710-089.0	343636	Maxima 36

Ground Force

- · Flip and fold handle
- · Choice of two or four nozzles
- · Rebuildable swivel
- 212°F
- 4-10 GPM
- Dimensions: 24" x 60" x 9"
- · Weight: 29 lbs



Whisper Wash Flat Surface Cleaners - continued

The "Big Guy"

- · Powder-coated aluminum housing
- · Oversized, self-lubricating twin thrust bearings
- · Choice of two or four nozzles
- 10" pneumatic tires, 4" caster
- · Crafted with durable stainless-steel and aircraft aluminum
- 212°F
- 4-10 GPM
- Dimensions: 28" x 44" x 12"

• weight: 48 lbs		
Part #	Original No.	Description
8.710-074.0	343606	Whisper Wash Big Guy Two Nozzles
8.710-075.0	343607	Whisper Wash Big Guy Four Nozzles
8.750-604.0	092110	Swivel, Complete Big Guy and Classic
8.701-879.0	092105	Repair Kit, Seal, Big Guy and Classic
8.701-874.0	092101	Spraybar, 4 Nozzle, Big Guy
8 701-876 0	092102	Sprayhar 2 Nozzle Big Guy

The Classic

- · Portable breakaway handle
- · ABS Housing
- 2" nylon brush
- 212°F
- 4-10 GPM
- Dimensions: 19" x 77" x 12"
- · Weight: 28 lbs



Part #	Original No.	Description
8.710-073.0	343605	Whisper Wash Classic
8.750-604.0	092110	Swivel, Complete Big Guy and Classic
8.701-879.0	092105	Repair Kit, Seal, Big Guy and Classic

The Ultra Clean WW

- ABS Housing
- . Four 3" casters
- · Powder-coated handle
- 185°F
- 3-6 GPM
- 2500 RPM
- Dimensions: 19" x 43" x 9"
- · Weight: 23 lbs



Part #	Original No.	Description
8.710-072.0	343604	Whisper Wash Ultra Clean WW



Whisper Wash Flat Surface Cleaners – continued

The Ultra Clean HC

- ABS Housing
- 2" nylon brush
- · Powder-coated handle
- 185°F
- 3-6 GPM
- Dimensions: 16" x 43" x 9"
- · Weight: 19 lbs

8.707-653.0



Part #	Original No.	Description
8.710-071.0	343603	Whisper Wash Ultra Clean HC
Repair Kits		
Part #	Original No.	Description
8.701-879.0	092105	Seal Kit; Classic, Big Guy and Ground Force
8.701-882.0	092108	Seal Kit; Ultra Clean
8.701-883.0	092109	Complete Swivel Kit; Ultra Clean
8.750-604.0	092110	Complete Swivel Kit; New Style Classic, Big Guy and Ground Force

2.5 x 25° 1/4" Nozzle Fits All Models

SideWinder Surface Cleaner

251119



- 2000-4000 PSI
- 12 GPM max
- 210°F

- · Heavy-duty aluminum handle
- 20" deck
- 19 lbs.

Part #	Original No.	Description
8.739-431.0	343690	SideWinder 105F Fixed Black

Mosmatic Gun Swivel



Mounts to your high-pressure gun or lance for an easy turning, low-maintenance gun swivel



- 4000 PSI
- 250°F
- 30 RPM

Part #	Original No.	Description
8.712-467.0	421057	1/4" MPT / 1/4" FPT Gun Swivel
8.712-466.0	421056	3/8" MPT / 3/8" FPT Gun Swivel

Mosmatic Surface Cleaners and Duct Cleaner

Turbo Surface Cleaner

Delivers high-pressure performance with low maintenance for any hot or cold pressure washer. Completely stainless-steel design makes this the toughest surface cleaner available in the pressure-cleaning market.



• 250°F

4000 PSI
 6.5 lbs.



250°F

• 2 lbs.

• 4000 PSI • Inlet Ports: 3/8" NPTF

Swiss-engineered with high RPM swivel features reinforced self-lubricated stainless-steel ball bearings and dual spring-based carbide seal bushings for long-lasting operation under tough conditions.

Ideal for pressure washer contractor to clean walls, ceilings, public facilities, tile floors and other hard-to-reach areas. Uses 1/8" meg 1503 nozzles.

Duct Cleaner

Designed as an accessory for use with highpressure pumps or pressure washers. Cleans ducts, chutes, vents, restaurant exhausts, tanks, etc.

Self-rotating and feeding stainless-steel triple bearing system for constant easy turning. Nozzle holders are 1/8" NPTF. Nozzles are sold separately.

12" Surface Cleaner

Designed for effortless cleaning of small areas, including walls and angled surfaces.

High RPM swivel with integrated toggle joint and adjustable tension system.

- 250°F
- 4000 PSI
- 9 lbs.
- 12" stainless-steel cover



Part #	Original No.	Description	PSI
8.712-284.0	411171A	Turbo Cleaner – 8"	4000
8.712-285.0	411172	Toggle Joint KGK	4000
8.712-280.0	411156	Duct Cleaner TXR-2s, Adjustable	4000
8.712-279.0	411155	Duct Cleaner TXR-2s, Fixed	4000
8.749-911.0		Surface Cleaner – 12"	4000

PRESSURE WASHER ACCESSORIES

Mosmatic Roof Cleaner



Industrial-quality tool specially designed for efficient, high-pressure roof cleaing while keeping the operator in a safe area.


- 21"
- 4000 PSI
- 250°F
- 31.9 lbs.
- Pressure gauge
- · Ball valve
- · Adjustable wheels (height and width)
- Safety eye connection for rope or cable
- Two 1/8" nozzles sold separately



Part #	Description
8.749-910.0	Mosmatic Roof Cleaner

Undercarriage Cleaner





- · Easy to handle and maneuver
- Removes road grime, fuel and oil contaminants
- Removes snow sludge and ice
- Provides a clean, working environment for technicians
- Stainless-steel rotating assembly built to withstand pressures up to 4000 PSI and 250°F
- 5.5" required clearance



Part #	Description
8.749-303.0	Undercarriage Cleaner

Kärcher Oil-Fired Hot Box

Add hot water cleaning economically! Portable water heater add-on for existing cold water pressure washers. Quick Connect to cold water washer, supply fuel and power to Euro-Heat for hot water cleaning applications — USE ONLY WHEN NEEDED and keep the convenience of the portable cold water washer.



- 3000 DC
- Quick hookup 3/8" QC inlet / outlet
- Easy service access to burner parts
- Efficient vertical combustion configuration
- · Diesel, kerosene, #1 heating oil
- 10" easy-roll tubed pneumatic wheels
- 5-gallon plastic fuel tank
- Compact size 37" W x 27" L x 39" H
- . 36' Ground Fault Interrupter plug
- · Thermostat temperature control

Part #	Original No.	Description
1.103-910.0		5 GPM / 3000 PSI - 120V

Goff's Curtain Walls

Build a Power Wash Cell to meet your needs. Goff's Curtain Walls™ increase useable floor space while controlling overspray, contaminants, climate, and noise levels. Curtain Walls™ glide easily on steel track and dual-wheeled rollerhooks. Made from a combination of 14-oz., heavy-duty, reinforced vinyl and double-polished 20-mil clear PVC material. Reinforced hems and chainweighted lower hems add durability. Hook and loop fasteners on side hems attach to adjacent panels. Meet NFPA-701 requirements for flame retardancy. Curtains are also rot and mildew resistant. Standard model has a white vinyl top, clear PVC center, and blue vinyl bottom.










- #2 Brass tooth grommets on 1' centers
- 14 oz. reinforced vinyl white top section
- All seams double-locked stitched
- Hook and Loop Fasteners allow adjacent panels to be easily attached to one another
- 20 mil. double-polished clear window
- All sections joined together using mildew/ rot resistant thread
- 14 oz. reinforced colored vinyl section (your choice of over 12 different colors)
- · Chain-weighted lower hem









Part #	Original No.	Description	PSI	
9.841-694.0	681133	6' width x 12' high	1500	
8.717-007.0	681083	12' width x 8' high	1500	
8.717-008.0	681084	12' width x 9' high	1500	
8.739-485.0	681082	12' width x 12' high	1500	
8.717-009.0	681086	24' width x 10' high	1500	
8.739-486.0	681087	24' width x 12' high	1500	
Station			•	
9.841-695.0	681145	4-sided x 12' high	1500	

Includes hardware, track and rollers (white top, clear center and blue bottom panel) All 2-, 3- and 4-sided stations are 12' wide x 24' long (see diagram above).

Other sizes available — call for details

Water Broom 16"





- 4000 PSI
- Fits any 1/4" wand
- Requires (4) 1/4" nozzles and wand

Part #	Original No.	Description
8.710-082.0	343615	Water Broom 16"

Professional Sandblast Head



- Long-wearing Carbide sand nozzle
- 1/4" FPT water inlet
- 200°F
- 10 GPM
- 3500 PSI
- Sand probe weight 6 oz, length 16"
- · Head weight: 13 oz

Nozzle Size	Part #	Original No.	
3.5	8.711-242.0	391631	
4.0	8.711-243.0	391632	
4.5	8.711-244.0	391633	
5.0	8.904-403.0	391634	
5.5	8.711-245.0	391635	
6.0	8.904-404.0	391636	
8.0	8.711-246.0	391637	

Part #	Original No.	Description	List Price
8.711-247.0	391640	Sand Probe	
8.901-264.0	121041	1/2" ID Polybraid Tubing, 25'	

Sandblast Kit - Carbide Nozzle Industrial Grade



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.



- 5500 PSI max working pressure
- 10 GPM max flow
- 200°F
- 10 lbs.
- · Nozzle tips sold separately

Part #	Original No.	Description
8.701-485.0	084079	Sand Blast Kit DWSDBTK

Sandblast Nozzles Tips



Replacement tips for Sandblaster Kit (part no. 8.701-485.0 – Original no. 084079)

• Use 1/4" meg 5° spray tip

Part #	Original No.	Description
8.707-668.0	251159	4.0 x 5° Tip
8.707-685.0	251198	5.0 x 5° Tip
8.707-696.0	251221	5.5 x 5° Tip
8.707-701.0	251237	6.0 x 5° Tip
8.707-709.0	251256	6.5 x 5° Tip

Sandblast Kit – Carbide Nozzle Industrial Grade



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.



8.701-617.0

- · Solid carbide blast nozzle
- · Venturi orifice design
- · Volume control sand feed valve
- Up to 3500 PSI
- Up to 750 lbs. of sand per hour

Kit contents: Sand head with carbide nozzle, 20" lance, sand probe, 13-1/2' sand hose, sand flow regulator valve.

Orifice Size	Part #	Original No.	
4.0	8.904-397.0	391554X	
4.5	8.904-396.0	391553X	
5.0	8.904-398.0	391555X	
5.5	8.904-395.0	391550X	
6.0	8.904-399.0	391556X	
7.0	8.904-400.0	391557X	
10.0	8.904-402.0	391560X	

Part #	Original No.	Description
8.701-620.0	086941	Solid Carbide Nozzle only
8.701-617.0	086930	Probe only

Tip-Jet Nozzles for water nozzle replacement or for system volume changes.

Orifice Size	Part #	Original No.	
3.0	8.708-016.0	253316	
4.0	8.708-019.0	253330	
4.5	8.708-023.0	253338	
5.0	8.708-027.0	253346	
5.5	8.708-031.0	253355	
6.0	8.708-035.0	253365	
6.5	8.708-039.0	253375	
7.0	8.708-042.0	253383	
7.5	8.708-046.0	253392	
8.0	8.708-050.0	253400	
9.0	8.708-054.0	253415	
10.0	8.708-058.0	253456	

Dual-Chemical Systems



- New deep-ribbed yellow casing, stays flexible even in cold temperature
- Hose assembly complete with gun and amphenol connectors pre-wired
- Fully-compatible with Power Blaster, Two-Step, Chemex and most other cold water dual-chemical systems

Part #	Original No.	Description		
Complete Hose A	ssembly			
8.709-044.0	285116	80' R2 Electric (5 wire)		
8.709-045.0	285120	100' R2 Electric (5 wire)		
Lance Attachment Parts				
8.709-049.0	285136	Female Receiver		
8.709-050.0	285137	Male Lance Swivel		
8.709-051.0	285138	Retainer Nut		
Complete Remote	Gun Unit			
8.709-046.0	285125	Gun, Electric		
Remote Gun / Hose Parts				
8.709-048.0	285135	Gun Housing		
8.709-053.0	285139	Switch P/B		
8.709-054.0	285140	Switch, Chemical		
8.709-056.0	285142	Switch Plate		
8.903-083.0	285144	O-ring, Nipple (Two req'd)		
8.903-084.0	285145	O-ring, Nipple (Bags of 50)		
8.709-060.0	285175	Swivel Adapter		
8.709-061.0	285177	Cord Grip		
8.709-063.0	285181	Oetiker clamp		
8.709-064.0	285187	Switch – Push Button Trigger		
8.709-065.0	285189	Toggle, DPDT (Trig) On/Off/On		

Stainless-Steel Sewer Nozzles



- 4100 PSI
- · Corrosion-resistant stainless-steel
- One forward orifice
- · Three rear orifices

Part #	Original No.	FPT	Size	
8.710-905.0	373075	1/8"	5.0	
8.710-906.0	373076	1/8"	5.5	
8.710-907.0	373077	1/8"	6.0	
8.710-908.0	373078	1/4"	6.5	
8.710-909.0	373079	1/4"	7.0	
8.710-910.0	373080	1/4"	9.5	

Sewer/Tube Cleaning Nozzles



The reverse jets on the fixed and rotary nozzles pull the hose through the tube or sewer line and blast debris from line or tube walls.



- · Backward ports drive the nozzle forward and flush debris
- Forward ports blast into pipe and breaks up clogs and debris
- · Physically small for cornering ability
- 4200 PSI
- Corrosion-resistant stainless-steel construction
- · Orifice size indicated on non-rotating styles
- · Rotating style adds extra agitation and surface cleaning

Part #	Original No.	Nozzle	Orifice Size	0.D.	Ports
Non-Rotating Sewer Nozzles					
8.710-875.0	373024	1/8"	4.5	.580"	0-forward, 3 back
8.710-874.0	373023	1/8"	5.5	.580"	1-forward, 3 back
8.710-878.0	373027	1/4"	4.5	.730"	1-forward, 3 back
8.710-876.0	373025	1/4"	5.5	.730"	1-forward, 3 back
8.710-877.0	373026	1/4"	6.0	.730"	1-forward, 4 back
8.710-880.0	373029	1/4"	7.5	.730"	1-forward, 4 back
8.710-879.0	373028	1/4"	8.0	.730"	1-forward, 3 back
8.710-881.0	373032	1/4"	12	.730"	1-forward, 3 back
8.710-885.0	373038	3/8"	4.0	.920"	1-forward, 3 back
8.710-884.0	373037	3/8"	5.5	.920"	1-forward, 3 back
8.710-886.0	373039	3/8"	8.5	.920"	1-forward, 4 back
8.710-883.0	373036	3/8"	12	.920"	1-forward, 4 back
8.710-882.0	373035	3/8"	14	.920"	1-forward, 4 back







0-forward, 3 back ports

1-forward, 3 back ports

1-forward, 4 back ports



- · Rotating sewer nozzle
- · Adds extra agitation
- 4000 PSI
- Back Jet Only

Part #	Original No.	Rotating Nozzle	Size	Ports
Rotating Sewer	Nozzles			
8.710-899.0	373062	1/8"	5.5	0-forward, 3 back
8.710-898.0	373061	1/4"	5.5	0-forward, 3 back
8.710-900.0	373064	1/4"	8.0	0-forward, 3 back
8.710-887.0	373040	1/4" Duct Clnr*	5.5	0-forward, 2 side

*Duct Cleaner jet to sides instead of reverse





0-forward, 3 back ports

0-forward, 2 side ports



PRESSURE WASHER ACCESSORIES

Sewer Hose

SUPER FLEXIBLE SEWER LINE HOSE Hose and couplings have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has Super Tough poly-ether cover over ultra-flexible nylon

tube. (1/8" sewer nozzle and hose will operate through many 1-1/2" lines.)


(Nozzles not included.)



- 160°F
- . Nylon tube, poly-ether cover

Part #	Original No.	Description	
1/8" hose – 4800 PS	SI, 1/4" inlet / 1/8" outlet		
8.705-601.0	150960	1/8" x 25'	
8.705-602.0	150963	1/8" x 50'	
8.705-603.0	150964	1/8" x 100'	
1/4" Hose – 2600 PS	SI, 1/4" inlet / 1/4" outlet		
8.705-607.0	150968	1/4" x 50'	
1/4" Hose – 4400 PS	GI, 1/4" inlet / 1/4" outlet		
8.705-610.0	150972	1/4" x 50'	
8.705-611.0	150973	1/4" x 100'	•
8.705-613.0 150975		1/4" x 200'	•

Foot-Controlled Pressure Valve SUTTNER W







- Inlet 3/8" outlet 1/4"
- · Brass body stainless-steel valve
- · Steel cover for safety
- Up to 12 GPM
- Up to 5000 PSI

Part #	Original No.	Description	PSI	
8.710-134.0	344200	Sewer Cleaner Foot Valve	3000	
8.709-972.0	342024*	Foot Valve w/ ST-2305	5000	
8.701-657.0	089006	Repair Kit – Foot valve		
8.701-673.0	089850	Repair Kit ST-2305		
8.711-526.0	4-0193	Kit, 25' Hose, #4.5 Nozzle, Fo	oot Valve	
*Heavy gauge steel construction for durability and stability				

ST-36 Pit Boss Sludge Sucker





Sludge Sucker uses a high-pressure water stream (1000-3000 PSI) to suck the sludge off the bottom of pits or tanks and eject it through a 1-1/2" (15' long) hose to a disposal tank.

The base unit attaches to the end of a pressure washer lance with a quick coupler for extension to the bottom of the pit. Uses a 0° tip for suction / power ejection.





- Uses standard 1/4" MPT nozzle
- · Easy to change for different plumbing system flows and pressures

Part #	Original No.	Description
8.711-112.0	376137	ST-35 Pit Boss, 5.5 Nozzle / 15' Hose
8.711-110.0	376126	(Base unit only)

^{*}w/o hose, nozzle or quick coupler (3/8" inlet port)

Drum Tool Accessories

The indispensable tools.







8.704-691.0





Part #	Orig. No.	Description	
8.712-534.0	449339	Drum Plug Wrench	
8.704-689.0	118400	Lid-Off	
8.704-691.0	118404	Funnel, 7" x 10"	
8.704-692.0	118407	3/4" Faucet	
8.704-693.0	118408	2" Faucet	
Load Cincher Tie	Load Cincher Tie Downs		
8.707-473.0	249938	7/8" x 5-1/2' (Non-Ratchet) "Quick Lock"	
8.707-474.0	249939	1" x 15' (Ratchet) "Tight Lock"	

Fiberglass "Super Handles"

- · Tough, durable, lightweight
- · No cracking, splintering
- · No kinks, dents
- · Safer around electrical hazards
- · Easy-twist cam lock extension
- · Super heavy-duty aluminum alloy threads
- Standard 3/4" Acme thread fits: brooms, brushes, utility tools
- Optional reduction adapter for 3/4" to Acme standard

Part #	Original No.	Description
Super Handles		
8.709-306.0	306864	48" Length (4 ft.)
8.709-307.0	306865	60" Length (5 ft.)
8.709-308.0	306866	72" Length (6 ft.)
Super-Extension H	landles	
8.709-309.0	306868	4 ft. to 8 ft. Ext.
8.709-310.0	306869	6 ft. to 12 ft. Ext.
8.709-311.0	306870	8 ft. to 16 ft. Ext.
8.700-308.0	075271	Threaded Adapter

Drum / Tank Pump - Crank Type

Chemical-resistant, lightweight pump, ideal for dispensing chemicals, pesticides and oils. Polypropylene for most alkalies, dilute acids, pesticides, and most oils and solvents. Ryton for extremely aggressive acids, aromatic and aliphatic hydrocarbons.



SPECIFICATION:

- 11 oz per revolution
- 6 GPM @ 70 RPM
- · Viton seals
- Polypropylene gasket
- 2" bung adapter
- · Outlet 3/4" barb two-piece
- 47" suction tube
- · Weight: 2.6 lbs

Part #	Original No.	Description
8.704-700.0	118435	Polypropylene Pump (Standard)
8.704-701.0	118438	Ryton Pump (Deluxe)
8.700-526.0	076975	Replacement Handles

Siphon Pumps

Siphon liquids from higher to lower levels. Simply pump the bellows a few times to prime and start flow. Loosen air lock to stop.



- Drum pump fits 15-, 30- and 55-gallon drums
- Fit 2" bung opening
- · Excellent for alkaline and acidic chemicals, diesel fuel, and oils
- · Not for use with solvents!

Part #	Original No.	Description
8.704-698.0	118429	Red Hex Head (Heavy-duty)
8.704-696.0	118423	Red Head (Standard duty)
8.704-694.0	118420	Pail Pump (5 Gallon)

Brushes



Rotating Brush - Natural Bristle (soft) used for painted surfaces. Nylon Bristle (stiff) used for removing scum and grime on fiberglass boats, etc.



• Internal nozzle = size 2	20
----------------------------	----

•	8	G٢	IV	ı

Part #	Original No.	Description	
Brush Unit Comp	lete		
8.709-312.0	306925	Natural	
8.709-314.0	306935	Nylon	
Replacement Brushes			
8.709-313.0	306927	Natural	
8.709-316.0	306937	Nylon	

Truck Wash Brush



- · Flag-tipped
- · Soft bristle
- . ACME thread for Super Handles, or broom handles

Part #	Original No.	Description	
8.709-298.0	306800	D6800 2-1/2" Bristle w/ Bumper x 10"	
8.709-303.0	306818	2-1/2" Bristle x 18"	
8.709-304.0	306824	2-1/2" Bristle x 24"	
8.709-305.0	306860	60" Flow Thru Lance*	
		·	

^{*}with Acme Thread and Garden Hose Attachment

Deck Scrub Brush - Over / Under

Unique heavy-duty scrub brush with multi-level / angle.



- Trimmed for cleaning hard-to-reach areas
- 10" molded polypropylene foam block does not warp or absorb water
- Stiff polypropylene bristle for aggressive cleaning
- · Excellent chemical resistance
- · Use with threaded handle
- Not a Flow Thru

Part #	Original No.	Description
8.709-302.0	306812	Deck Scrub Brush

Tractor Brush - Soft for gentle cleaning of fine finishes.



Part #	Original No.	Description
8.709-300.0	306802	Flag Tip Window 10"

PRESSURE WASHER ACCESSORIES

Compact Foamer



Generates a high-density clinging foam for extended dwell-time to increase chemical action.



- Stainless-steel, aluminum and
- 5" long, 1" diameter
- included 1 to 5 GPM

4 and 6.5 nozzle

- 195°F
- 2500 PSI

Part #	Original No.	Description
8.903-998.0	344022V	1/8" F Inlet
8.903-999.0	344023V	1/4" F Inlet

NOTE: Most cleaning chemicals perform best when applied at 120°-150°F and can be applied as a foam by adding a foaming agent. See your chemical supplier to obtain the correct product.

Foam Cannon

The ideal Foam Generator Application Accessory meters the foaming chemical for customized foam type and applies the foam to match the application.



- · High-impact, glass-filled body
- · 176°F max temperature
- 1/4" FPT lance connect

Part #	Original No.	Description
8.710-125.0	344030 Foam Cannon / Injector	
8.710-126.0	344032	Foam Cannon / Injector / Bottle
8.704-222.0	113011	Replacement Turbulator Screen

Air-Power Sprayers



- · Pump-up style
- · Heavy-duty plastic sprayers for chemical applications
- Both models have Adj. Nozzle from mist to solid stream
- . 2-gallon unit has 2' hose and hand trigger
- · Excellent chemical resistance
- · Locking hand pump handle serves as carrying handle

Part #	Original No.	Description
8.704-703.0	118842	Thumb Button 3 Pint
8.704-702.0	118835	2-Gallon Sprayer

Foam Jet Kit



Long-distance foam applicator. Shoots OVER 20 FEET of dense foam. Suction at 30 feet of height. Varable spray pattern.



- 5000 PSI
- 5.6 GPM
- 14" inlet
- 140°F
- 33' Tube

Part #	Description
8.750-296.0*	Kit, Foam Jet, 5000 PSI, 5.6 GPM
8.750-429.0	Kit, Repair, Foam Jet Orings / Stainless-Steel Filter
8.750-430.0	Kit, Repair, Foam Jet, Hose / Valve / Filter

* Includes tubing and fittings as shown

Lafferty Airless Foam Kit



- · Machined stainless-steel construction
- · Stainless-steel chemical check valve
- · Stainless-steel quick disconnects
- . 10' chemical tube with strainer
- Color-coded metering tips for up to 21 dilution ratios
- · 0° nozzle for increased foam-throw distance

Part #	Water Flow Rate	@2000 PSI	@ 137.9 bar
8.749-908.0	Model 10	4.0 GPM	15.1 LPM
8.749-909.0	Model 20	6.0 GPM	22.7 LPM

Adjustable Foamer with Tank

Control the foam spray angle with the variable fan nozzle.



- · Horizontal variable fan nozzle
- GPM: 5.3
- · Foam control adjustment knob
- 140°F
- PSI: 2600

Part #	Description
8.710-124.0	Adjustable Foamer w/ Tank



Thread Lock Products



- Direct replacement for LocTite® and Fel-Pro™ products
- ND™ anaerobic adhesives are liquid materials that cure to a solid, chemical-resistant plastic state when air is not present
- · Excellent lubricant; prevents corrosion and fretting

Part #	Original No.	Description	LocTite® Equiv	Bottle Size	
8.704-644.0	112350	Nut Grade™	242	10 ml	
8.704-645.0	112352	Nut Grade™	242	50 ml	
8.704-646.0	112354	Nut Grade™	242	250 ml	
8.704-648.0	112360	Stud Grade™	271	10 ml	
8.704-649.0	112362	Stud Grade™	271	50 ml	
8.704-650.0	112367	Penetrating Adhesive (Sealant)	290	10 ml	

Nut $Grade^{\infty}$ and $Stud\ Grade^{\infty}$ are trademarks of the Oakland Corp. LocTite $^{\circ}$ is a registered trademark of the LocTite Corp.

Gloves - Industrial Duty

Industrial-grade gloves for most industry-needs — chemical / heat / abrasion / laceration protection.



Black, 14" PVC glove lined with cotton for the most demanding chemical handling. Resists alkalines, acids — even works well as a sandblasting glove.

8.704-668.0 Gray – Split Cowhide work gloves, 2-1/2" gauntlet unlined — great general purpose work glove.

Part #	Original No.	Description
8.704-668.0	116105	Gray Roughout
8.704-669.0	116114	Black PVC

Rain Suit - 2-Piece



Part #	Original No.	Description
8.704-666.0	116100	Large
8.704-667.0	116101	Extra Large

Amazing Pocket Reference – Third Edition

A ton of information in a 5 oz book!



- · Air and gases
- Automotive
- Chemistry
- Electrical
- Physical constants
- · Math
- · 3350 conversion factors
- · Plumbing and pipe
- Over 20 other subject areas

Part #	Original No.	Description
8.712-505.0	449015	Pocket Reference

Shipping Tape and Dispenser

Big $2^{\prime\prime}$ x 110 yard rolls of clear. Biaxially-oriented polypropylene for secure packages.





Heavy-duty tape dispenser with serrated blade

Part #	Original No.	Description
8.704-707.0	118916	Dispenser Boxed
8.901-249.0	118918	110 Yard Roll

Teflon® Thread Sealing Tape



- Big 1/2" x 520" roll
- Mil spec #T27730

Part #	Original No.	Description	
8.704-705.0	118905	Thread Sealing Tane	