

LORCHEM ACID FOAMERS are designed for use with strongly corrosive chemicals, such as those used in the concrete industry and for aluminum brightening. They are water-driven, air-assisted venturi systems that accurately dilute chemical concentrates to the required ratios and project high quality foam onto any surface.

Choice of 1-Way, 2-Way and 3-Way models and three flow rates – all capable of achieving strong chemical ratios.

ACID LV FOAMERS

REQUIRES: 40-125 PSI WATER, COMPRESSED AIR & CHEMICAL CONCENTRATE

- Low Volume output for precise foaming applications
- Draw concentrate directly from original shipping containers and accurately dilute it to the required ratio
- Covers up to 500 ft² (46.5 m²) in 4 ½ minutes
- Usable foam throw distance of up to 9 feet
- Choice of 1-Way, 2-Way and 3-Way models

REQUIREMENTS / SPECIFICATIONS


Compressed Air	2.5 - 6 cfm	70.8 - 169.9 lpm
Water Pressure	40 - 125 psi	2.6 - 8.6 bar
Water Flow Rate	@ 40 psi	@ 2.6 bar
	0.65 gpm	2.4 lpm

Discharge Hose

ID	3/4 in.	19.1 mm
Length	40 ft.	12.2 m

Includes

- Machined polypropylene foamer body
- Polypropylene mounting plate and cover
- Color-coded metering tips for up to 21 dilution ratios
- Discharge hose assembly with PVC ball valve, extended wand and fan nozzle



Model #	Description
972306-LV	1-Way Acid LV Foamer Complete
972307-LV	2-Way Acid LV Foamer Complete
972308-LV	3-Way Acid LV Foamer Complete



ACID LC FOAMERS

REQUIRES: 40-125 PSI WATER, COMPRESSED AIR & CHEMICAL CONCENTRATE

- Medium Volume output for all foaming applications
- Draw concentrate directly from original shipping containers and accurately dilute it to the required ratio
- Covers up to 500 ft² (46.5 m²) in 2 minutes
- Usable foam throw distance of up to 12 feet
- Choice of 1-Way, 2-Way and 3-Way models

REQUIREMENTS / SPECIFICATIONS


Compressed Air	2.5 - 6 cfm	70.8 - 169.9 lpm
Water Pressure	40 - 125 psi	2.6 - 8.6 bar
Water Flow Rate	@ 40 psi	@ 2.6 bar
	1.3 gpm	4.9 lpm

Discharge Hose

ID	3/4 in.	19.1 mm
Length	40 ft.	12.2 m

Includes

- Machined polypropylene foamer body
- Polypropylene mounting plate and cover
- Color-coded metering tips for up to 21 dilution ratios
- Discharge hose assembly with PVC ball valve, extended wand and fan nozzle



Model #	Description
972306	1-Way Acid LC Foamer Complete
972307	2-Way Acid LC Foamer Complete
972308	3-Way Acid LC Foamer Complete

