

# NEPTUNE 4-36 FAX

*Superior hot water technology and performance*

[www.nilfisk-alto.us](http://www.nilfisk-alto.us)



## **Big Things Can Come in Small Packages**

Many years of experience have given us the knowledge necessary to build a superior machine for users who need reliable and effective performance, even in smaller settings.

You don't have to sacrifice versatility OR performance with the Neptune 4 series. It's small, but it can do more than many larger machines.

# Nilfisk ALTO

## Key Features & Benefits

- Equipped with our new Nilfisk-ALTO “NA5” pump with KEW Technology. Brass pump and cylinder head, solid ceramic pistons, and our unique flow activated unloader valve ensures years of trouble free operations.
- The Neptune 4-36 FAX comes with a built-in hose reel and 50 feet of hose for added operator convenience and value.
- Our Nilfisk-ALTO ECO Burner system is unmatched in the marketplace. With a 92% efficiency it saves up to 30% in fuel consumption over conventional burner types.
- Built-In “Anti Leak Function” automatically detects small water leaks in the system and prevents “false starts” thus prolonging the life of the pressure washers.
- Time delayed Automatic Start/Stop ensures convenience, longer life, and lower maintenance costs.
- Standard flame sensor and exhaust gas temperature sensor ensures that the machine is protected against burner errors.
- Our unique “Low Fuel” detection system protects the burner system and fuel pump and prevents costly service bills.
- All of our pressure washers are equipped with the most ergonomic spray equipment. Low activation and holding force on the trigger gun reduces physical strain, as does the ideal design of our cleaning wands.

TECHNICAL DATA	NEPTUNE 4-36 FAX
Part Number	107146618
Pressure (Max pump pressure)	2,500 PSI
Water Flow (Max)	3.0 GPM
Power (P/V/A)	1 x 230 V, 25 A
Motor - (TEFC)	5.0 hp
Delayed Automatic Start/Stop (30 sec)	Yes
KEW Ergo 2000 Gun	Yes
Tornado 3000 Lance	Yes
KEW Tornado Nozzle	0400
Adjustable Thermostat	Yes
Built-in Chemical Injector	Yes
Ceramic Pistons	Yes
Brass Pump & Cylinder Head	Yes
Low Fuel Detection	Yes
Low Pump Oil Protection	Yes
Water Temp (water/steam)	180 °F / 302 °F
Fuel Consumption (ΔT at 115°F)	1.0 gal/hour
Fuel Tank	6.5 gal
Detergent Tank	2.5 gal
Dimensions (LxWxH)	42 in x 27 in x 30 in
Weight	275 lb

# Nilfisk ALTO


### Nilfisk-ALTO

14600 21st Avenue North • Plymouth, MN 55447-3408  
 Phone: 877.366.2586 • Fax: 800.405.9092  
[info@altocsi.com](mailto:info@altocsi.com) • [www.nilfisk-alto.us](http://www.nilfisk-alto.us)

©2010 Nilfisk-Advance All Rights Reserved. Specifications subject to change without notice. P/N L105NALTO 6-23-10

# EcoPower

Clean Performance



## 92% FUEL EFFICIENCY

### Earth Friendly, Wallet Friendly

The new EcoPower Boiler system developed by Nilfisk-ALTO is more than 92% fuel efficient, which means you're saving the environment AND your money.



Because the boiler operates with cleaner combustion, soot build-up is lessened, reducing boiler maintenance and saving fuel costs. That means you have less down time and fewer man hours spent on maintenance.

## Simplicity Embraces Functionality

Having the controls in one place makes life easy



- Single knob for starts, stops and temperature adjustments
- Detergent dosing control includes self-cleaning feature for reduced maintenance
- LED indicators for:
  - Power
  - Low Pump Oil
  - Service Reminder
  - Low Anti-Scale Level
  - Low fuel

### Easy to Transport

Because of its small size, the Neptune 4 series machines are easy to load and transport.

**Lorchem Technologies, Inc.**

1150 Davis Road, Suite J, Elgin, IL 60123  
 P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811  
[www.lorchem.com](http://www.lorchem.com) • [info@lorchem.com](mailto:info@lorchem.com)

We Know How To Get Things **CLEAN**