

NEPTUNE 5-50 FAX

Superior hot water technology and performance

www.nilfisk-alto.us



Big Things Can Come in Small Packages

Many years of experience have given us the knowledge necessary to build a superior machine for users who need reliable and effective performance, even in smaller settings.

You don't have to sacrifice versatility OR performance with the Neptune 5 series. It's small, but it can do more than many larger machines.



**Nilfisk
ALTO**

works for you

Key Features & Benefits

- Equipped with our new Nilfisk-ALTO “NA5” pump with KEW Technology. Brass pump and cylinder head, solid ceramic pistons, and our unique flow activated unloader valve ensures years of trouble free operations.
- The Neptune 5-50 FAX comes with a built-in hose reel and 50 feet of hose for added operator convenience and value.
- Our Nilfisk-ALTO ECO Burner system is unmatched in the marketplace. With a 92% efficiency it saves up to 30% in fuel consumption over conventional burner types.
- Built-In “Anti Leak Function” automatically detects small water leaks in the system and prevents “false starts” thus prolonging the life of the pressure washers.
- Time delayed Automatic Start/Stop ensures convenience, longer life, and lower maintenance costs.
- Standard flame sensor and exhaust gas temperature sensor ensures that the machine is protected against burner errors.
- Our unique “Low Fuel” detection system protects the burner system and fuel pump and prevents costly service bills.
- All of our pressure washers are equipped with the most ergonomic spray equipment. Low activation and holding force on the trigger gun reduces physical strain, as does the ideal design of our cleaning wands.

TECHNICAL DATA	NEPTUNE 5-50 FAX
Part Number	107146665
Pressure (Max pump pressure)	2,100 PSI
Water Flow (Max)	4.5 GPM
Power (P/V/A)	1 x 230 V, 30 A
Motor - (TEFC)	7.0 hp
Delayed Automatic Start/Stop (30 sec)	Yes
KEW Ergo 2000 Gun	Yes
Tornado Plus Lance	Yes
KEW Tornado Nozzle	0700
Adjustable Thermostat	Yes
Built-in Chemical Injector	Yes
Ceramic Pistons	Yes
Brass Pump & Cylinder Head	Yes
Low Fuel Detection	Yes
Low Pump Oil Protection	Yes
Water Temp (water/steam)	180 °F / 302 °F
Fuel Consumption (ΔT at 115°F)	1.1 gal/hour
Fuel Tank	9 gal
Detergent Tank	6.5 and 2.5 gal
Dimensions (LxWxH)	45 in x 28 in x 39 in
Weight	405 lb

Nilfisk ALTO


works for you

14600 21st Avenue North • Plymouth, MN 55447-3408
Phone: 877.366.2586 • Fax: 800.405.9092
info@altocsi.com • www.nilfisk-alto.us

©2013 Nilfisk-Advance All Rights Reserved. Specifications subject to change without notice. P/N L108NALTO 4-25-13

EcoPower

Clean Performance



92% FUEL EFFICIENCY

Earth Friendly, Wallet Friendly

The new EcoPower Boiler system developed by Nilfisk-ALTO is more than 92% fuel efficient, which means you're saving the environment AND your money.



Because the boiler operates with cleaner combustion, soot build-up is lessened, reducing boiler maintenance and saving fuel costs. That means you have less down time and fewer man hours spent on maintenance.

Simplicity Embraces Functionality

Having the controls in one place makes life easy



- Single knob for starts, stops and temperature adjustments
- Detergent dosing control includes self-cleaning feature for reduced maintenance
- LED indicators for:
 - Power
 - Low Pump Oil
 - Service Reminder
 - Low Anti-Scale Level
 - Low fuel

Lorchem Technologies, Inc.

1150 Davis Road, Suite J, Elgin, IL 60123
P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811
www.lorchem.com • info@lorchem.com

We Know How To Get Things **CLEAN**