



## **A15 EXP/A15 EXP W**



## Hazardous Location Vacuums



Nilfisk CFM's line of pneumatic hazardous location vacuums feature two separate models to meet all your cleaning needs. The A15 EXP is designed for dry material collection while the A15 EXP W is equipped for picking up liquids and other wet hazardous materials. Both vacuums meet the requirements for use in Class I, Group D, and Class II, Groups E, F, and G environments. The units are made of 304 stainless steel and feature optional HEPA or ULPA filtration.

- Powered by compressed air for use where electricity is undesirable or unavailable.
- All stainless steel construction including container, filter chamber and trolley.
- Equipped standard with 50-foot air supply hose.
- Antistatic filter with large surface area and external filter shaker in the A15 EXP guarantees high filtration efficiency and prevents premature clogging.
- Optional downstream HEPA/ULPA filtration available on both units; Upstream HEPA available for dry model only. HEPA filter retains 99.97% of particles, down to and including 0.3 microns. ULPA retains 99.999% down to and including 0.12 microns.
- Non-sparking, conductive accessories are available to meet a wide range of hazardous cleaning needs.
- For more information on combustible dust preventative maintenance, visit our focus site, [www.explosionproof-vacuum.com](http://www.explosionproof-vacuum.com).

Technical Features		A15 EXP	A15 EXP W
Waterlift, Max in H2O	inches	157	157
Airflow, Max	cfm	99	99
Tank Capacity	gallons	6.6	13.2
Main Filter Area	sq. ft.	8.8	8.8
Dimensions	inches	20 x 24 x 40	20 x 24 x 40
Weight	lbs.	53	61
Sound Level	dB(A)	72	72
Air Consumption @ 90 psi	cfm	30	30
Min. Compressor Requirement	hp	7.5	7.5
Machine Inlet, Diameter	mm/inches	50/2.0	50/2.0
Compressed Airline, Diameter	inches	1/2	1/2
Compressed Airline, Length	feet	50	50
HEPA filter efficiency (DOP-tested)	%	99.97% @ 0.3 microns	99.97% @ 0.3 microns
ULPA filter efficiency (DOP-tested)	%	99.999% @ 0.12 microns	99.999% @ 0.12 microns

\*Collection of commercial alloys is subject to individual approval by our application engineer. Specifications may change without notice.



A15 EXP



Remove combustible dust and debris from hazardous locations



Easy to remove wheeled collection container on A15EXP



Optional downstream HEPA/ULPA filter on A15EXP, dry unit



External filter shaker on A15 EXP for dry material collection



Both models feature antistatic, conductive accessories for ultimate safety

Distributed by:



1150 Davis Road, Suite J, Elgin, IL 60123  
P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811  
www.lorchem.com • info@lorchem.com

We Know How To Get Things **CLEAN**