



T26 - T48 - T63 Industrial Vacuums



Solid. Reliable. Effective.

Nilfisk CFM T Series: Three-phase Industrial Vacuums



T Series



Introducing Nilfisk CFM's new generation of three-phase industrial vacuums, the T Series. Comprised of the T26, T48 and T63, these reliable machines feature solid construction and strong performance at an affordable price. Ideal for collection of powders, liquids, dust and debris, the vacuums are easy to use and maintain - even in the most challenging environments.

- Lightweight and highly maneuverable, the T Series vacuums feature rear swiveling wheels with locking brakes.
- A unique release lever lowers the wheeled collection container and acts as a handle for fast and easy disposal of collected debris.
- An optional HEPA filter ensures that 99.995% of particles are retained, down to and including 0.18 microns in size. This exceeds HEPA filter standards.
- The T26, T48 and T63 are compatible with a wide range of Nilfisk CFM attachments and hoses to meet specific application requirements. For example, a 40 liter swarf basket and wet shut-off valve are available for metalworking applications.

Description	Units	T26	T48	T63
Voltage @ 60Hz	Volts	200-240/440-480	200-240/440-480	200-240/440-480
Power, max	kW	2.6	4.8	6.3
Waterlift, max	Inches H2O	82.6	140.5	82.6
Airflow, max	cfm	222.4	222.4	345.3
Filter Area, main	Square ft.	21	21	21
Filter Area, optional HEPA	Square ft.	37.7	37.7	37.7
Noise Level, 3' 3" (1 meter)	dB(A)	71	74	74
Protection Class	IP	55	55	55
Insulation Class	Class	F	F	F
Tank Capacity	Gallons/liters	26 /100	26 / 100	26 / 100
Machine Inlet	mm	70	70	70
Cord Length	Feet	30	30	30
Filter Efficiency, HEPA	MPPS tested	99.995% @ 0.18 microns	99.995% @ 0.18 microns	99.995% @ 0.18 microns
Dimensions (L x W x H)	inches	44.5 x 23.6 x 60.2	44.5 x 23.6 x 60.2	44.5 x 23.6 x 60.2
Weight	lbs	251.3	297.6	306.4

* Specifications are subject to change without notice.

Construction: The T Series is constructed of heavy duty steel and polypropylene.

Filtration systems: The main filter is available in Standard Polyester, Polyurethane or PTFE Membrane, Nomex (high-temperature) and Antistatic. Oversized versions are also available.

Filter cleaning systems: The T series machines come standard with a manual filter shaker that quickly removes caked on dust from the filter's surface, maintaining the vacuum's maximum suction power and improving productivity.

Collection options: For safe collection and easy disposal, the T26, T48 and T63 are available with a dust bag, safe bag, or Longopac® Collection System, which allows for the collection of material in an "endless" bag that can be filled with the desired quantity, cut, sealed, disposed and immediately restored for a new use.



Liquid cut-off system (optional)



Manometer



Optional HEPA Filter



Longopac® Collection System



Distributed by:



1150 Davis Road, Suite J, Elgin, IL 60123
 P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811
 www.lorchem.com • info@lorchem.com

We Know How To Get Things **CLEAN**