Nilfisk GWD 255 Drum-Top Vacuum



Designed to meet the general plant cleaning and maintenance needs of industrial manufacturers, the Nilfisk GWD 255 wet/dry drum-top vacuum is powered by two independent bypass motors and can fit both 30 and 55 gallon drums, allowing users to recycle drums that are abundant in nearly every production plant.

- Washable main sack filter extends filter life
- Fifty-foot yellow safety cord for ultimate safety
- An optional float chamber and washable cartridge filter allows the GWD 255 to pick up both wet and dry materials
- Upstream HEPA filter available for pick-up of hazardous materials, ensuring 99.97% of particles are retained, down to 0.3 microns
- 38 mm or 50 mm accessory kits are available to meet a wide range of cleaning needs

For more information, contact our customer service department at 1-800-645-3475 or visit www.NilfiskIndustrialVacuums.com.



Nilfisk GWD 255

Drum-Top Vacuum



Specifications

Units	GWD 255
volts	110-120
watts	1800
amps	2
inches of H2O	80
cfm	220
feet	50
DOP-tested	99.97% @ 0.3 microns
	volts watts amps inches of H2O cfm feet



*Specifications are subject to change without notice / drum and trolley sold separately.

Distributed by:



1150 Davis Road, Suite J, Elgin, IL 60123 P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811 www.lorchem.com • info@lorchem.com