



ELIMINATOR SERIES
WET/DRY VACUUMS

DURABLE WET/DRY CLEANING FOR RUGGED ENVIRONMENTS



Eliminator vacuums are designed to withstand regular use in rugged applications, while maintaining strong suction and filtration. They come standard with multi-stage filtration featuring a disposable bag, main filter and DOP-tested HEPA filter.

The Eliminator I standard model, is configured for dry collection but can easily be converted into a wet/dry vacuum by adding a float chamber device (factory installed units available).

The versatile Eliminator Pro II is ideal for wet or dry collection of dust and debris. A 12-gallon collection container and efficient motor ensure minimal maintenance upkeep.

TECHNICAL SPECIFICATIONS	ELIMINATOR I		ELIMINATOR PRO II
	Dry	Wet/Dry	Wet/Dry
Collection type	Dry	Wet/Dry	Wet/Dry
Voltage @ 60 Hz	120 V		120 V
Type of power	1-phase		1-phase
Power @ 60 Hz	1.8 HP (1350 W)		1.3 HP (1000 W)
Current, max.	11.2 amps		8.5 amps
Airflow, max.	89 CFM (2520 L/min)		130 CFM (3681 L/min)
Waterlift, max.	88 in. H ₂ O (2235 mm H ₂ O)		89 in. H ₂ O (2260 mm H ₂ O)
Bag Capacity	3.4 gal. (13 L)		7.25 gal. (27 L)
Tank Capacity	5 gal. (19 L)	3.6 gal. (14 L)	12 gal. (45 L)
Main Filter Area	1.45 ft. ² (.13 m ²)		1.45 ft. ² (.13 m ²)
HEPA Filter Area, upstream	6.99 ft. ² (.65 m ²)		6.99 ft. ² (.65 m ²)
HEPA Filter Efficiency	99.97% @ 0.3 microns		99.97% @ 0.3 microns
Inlet Diameter	38 mm		58 mm
Dimensions (L x W x H)	17.0 in. x 16.0 in. x 22.0 in. (432 mm x 406 mm x 559 mm)		26.5 in. x 17.25 in. x 36.5 in. (673 mm x 438 mm x 927 mm)
Weight	20 lb. (9 kg)		35 lb. (16 kg)
Cord Length	50 ft. (15 m)		50 ft. (15 m)
Sound Pressure Level @ 3'3"	64 dB(A)		66.7 dB(A)

Specifications subject to change without notice. The data, characteristics, colors and illustrations are merely indicative and therefore not binding.



Tilting Motor Head on Eliminator Pro II



Three-Stage Filtration System



Eliminator I Standard Accessory Kit



1150 Davis Road, Suite J, Elgin, IL 60123
 P: (847) 468-8800 • (800) 788-8867 • F: (847) 468-8811
www.lorchem.com • info@lorchem.com

