

SEA

Stationary, Electric-Powered, Cold Water Pressure Washer

- Up to 4.2 GPM
- Up to 3000 PSI
- Stainless Steel or Mild Steel Cabinet
- Accepts Hot Water Up to 185°F

■ **Industrial-Grade Motor** is connected to the rugged, class-leading, tri-plunger, oil-bath **LT** (stainless steel model) or **LM** (mild steel model) **High-Pressure Pump** (with 7-year warranty) by dual, V-cogged belts. **Pulleys** are made of cast iron and can be easily adjusted by turning two bolts.

■ Four quick-couple **Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 0°, 15°, 25°, 40°.

■ Heavy-duty **Cabinet** rides on four **Rubber Feet** for absorption of vibration.

▶ Add portability to the SEA with optional **Wheel Kit** (stainless steel model #8.904-527.0 or mild steel model #9.801-031.0), including detergent jug holder. Optional **Hose Reel** (#8.903-521.0) provides tangle-free handling of up to 100 ft. of high-pressure hose.



■ Many **Safety Features**, including a thermal pump protector to prevent the buildup of excessive pressures or heat.



SEA3-11024D

Shown with stainless steel cabinet



■ **Inlet Filter** strainer protects pump from debris.

■ 50 ft. of double steel-wire braid **High Pressure Hose** with 24-inch **Hose Guard** for burst protection and swivel crimp fitting for tangle-free handling of hose and trigger gun.



SEA3-11024D

Shown with mild steel cabinet

■ Easy-to-attach **Detergent Injector** for easy application of soap.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ **Time-Delay Shutdown** (stainless steel model only) automatically turns off unit, if not in use for a set time, for protection against unattended operation.

■ With the switch in the 'ON' position, the optional **Auto Start/Stop** function allows the unit to be turned on with the pull of the trigger for convenient remote operation. (This option replaces Time-Delay Shutdown.)

■ Insulated, fatigue-free, spring-loaded, 5000 PSI **Trigger Gun** with dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.

■ Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection (stainless steel model only and cannot be ordered with wheel kit option).

■ 36 ft. of high-grade **Electrical Cord** with **Ground Fault Circuit Interrupter** (on single-phase models) for operator safety.

■ **Compact Design**, 26" L x 20" W x 16" H.

■ Easily handles **Water Up To 185°**.



WHY CHOOSE THE SEA

The SEA is the absolute top-of-the-line stationary, cold water pressure washer on the market today. All stainless steel models are belt driven with top-quality pumps, and feature time delay shutdown or optional auto start/stop. Mild steel models are available with either features as an option. Remote operation is available with the LanCom wireless remote control option.

QUALITY: Only the highest quality components are found in the SEA, including a tri-plunger high pressure pump with a 7-year warranty, stainless steel or mild steel cabinet riding on four vibration absorbing feet, and stainless steel variable pressure wand for maximum cleaning flexibility. Also, the SEA is assembled in a factory certified to the internationally recognized ISO-9001 quality standards.

SAFETY: The SEA is certified to the rigid UL-1776 and CSA C22.2 #68 safety standards. It also meets the National Electric Code (NEC), Canadian Electric Code (CEC), and complies with OSHA Regulation 1910.399, making it very safe to operate. The SEA comes equipped with magnetic contactor switch with thermal overload protection, time-delay shutdown (stainless steel model), 24-inch hose guard for burst protection, ground fault circuit interrupter on all single-phase models, and tri-lingual operating instructions.

APPLICATIONS: The SEA is the perfect cleaning solution for use within the food service and automotive industries. If hot water cleaning is required, it can easily pair with our EHW, NG, and HS heating modules.

Model #	Part #	Cabinet	GPM	PSI	Pump RPM	Motor HP	Volts	Phase	Amps	Ship Wt (lbs)
SEA3-11024D	1.106-500.0	stainless steel	2.8	1000	1540	2.0	120	1	20	205
SEA4-20024A	1.106-501.0	stainless steel	4.2	2000	1013	6.2	230	1	28	280
SEA4-20024B	1.106-502.0	stainless steel	4.2	2000	1013	6.2	230	3	16	220
SEA4-20024C	1.106-503.0	stainless steel	4.2	2000	1013	6.2	460	3	7.2	220
SEA4-20024G	1.106-505.0	stainless steel	4.2	2000	997	6.2	208	1	30	297
SEA4-20024H	1.106-506.0	stainless steel	4.2	2000	1028	6.2	208	3	18.5	220
SEA4-30024B	1.106-507.0	stainless steel	3.5	3000	943	7.5	230	3	21.5	235
SEA4-30024C	1.106-508.0	stainless steel	3.5	3000	943	7.5	460	3	10.5	235
SEA3-11024D	1.106-583.0	mild steel	2.8	1000	1500	2.0	120	1	20	210
SEA4-20024A	1.106-584.0	mild steel	4.2	2000	1281	6.2	230	1	29	285
SEA4-20024B	1.106-585.0	mild steel	4.2	2000	1281	6.2	230	3	11	255
SEA4-20024C	1.106-586.0	mild steel	4.2	2000	1281	6.2	460	3	11	260
SEA4-20024H	1.106-587.0	mild steel	4.2	2000	1281	6.2	208	3	16	265
SEA4-30024B	1.106-588.0	mild steel	3.5	3000	1070	7.5	230	3	19	275
SEA4-30024C	1.106-589.0	mild steel	3.5	3000	1070	7.5	460	3	11	270

Field Installed Options & Accessories

All Models

9.801-036.0	Cox Hose Reel Kit (floor stand / wall mount)	9.801-031.0	Wheel Kit with Detergent Rack
8.903-521.0	E-Zee Hose Reel & Mounting Kit (fits wheel kit)	8.903-040.0	24" Floor Stand
9.802-265.0	Hose Reel, Mini, (fits wall bracket, 150' capacity)	9.801-034.0	36" Floor Stand
8.711-860.0	Hose Reel, Mini (fits wall bracket, 100' capacity)	8.903-617.0	36" Floor Stand (stainless steel)
9.801-035.0	Wheel Kit (4 casters)		

Mild Steel Models Only

9.801-011.0	Auto Start/Stop ♦*
9.801-013.0	Hour Meter ♦
9.801-012.0	Time Delay Shutdown ♦
9.801-033.0	Wall Mount Bracket Assembly

Distributed by:



1150 Davis Road, Suite J ▪ Elgin, IL 60123
(800) 788-8867 ▪ info@lorchem.com ▪ lorchem.com

We Know How To Get Things **CLEAN**

Stainless Steel Models Only

8.930-163.0	LanCom Wireless Remote Control, 1-Step Detergent ♦◊
8.930-177.0	LanCom Wireless Remote Control, 2-Step Detergent ♦◊
8.903-461.0	Remote On/Off Switch Option (Time Delay units only) ♦ ◊
8.930-358.0	Additional LanCom Remote
8.903-619.0	Wall Mount Bracket Assembly
8.930-131.0	Wall Mount Bracket for Fixed LanCom Remote
8.903-511.0	Auto Start/Stop (Replaces Time Delay Shutdown) ♦◊
8.904-527.0	Wheel Kit with Detergent Rack (stainless steel)*
8.903-448.0	Float Tank Option with Inlet Soap Injection ♦*◊

- ♦ Factory Installed
- ♦◊ Not compatible with LanCom
- * Float Tank cannot be ordered with Wheel Kit
- ◊ Not compatible with Auto Start/Stop or Float Tank options